




# Guided Wave Radar Level Transmitter



# PRODUCT INTRODUCTION

## OPERATING PRINCIPLE

The guided wave radar level transmitter is a solid and liquid level measuring instrument commonly used in the industry. It transmits electromagnetic pulses along with the steel wire cable or rod ; when these encounter the surface of medium to be measured, the pulses will be partly reflected to form an echo wave and returned to the pulse transmission device along the same path, and the height of liquid level can be calculated.

The guided wave radar level transmitter uses advanced echo wave processing technology with a wide range of product applications that is capable of measuring the low dielectric constant of solid buck; and capable of measuring the solid level, liquid level and medium surface. The product models include coaxial, tube/rod, steel wire cable type for the customer's choice, suitable for high temperature and high pressure medium liquid level measurement.

## FEATURES

- Applicable for various measurement requirements of different temperature, pressure and medium.
- Contact measuring, capable of overcoming the steam, foam and stirring effects.
- 4~20 mA / 2 lead wires, simple wiring, low power consumption (2.4W max.).  
128\*64 LCM Display, easy on-site adjustment.
- Display distance, level, percentage, current 4~20 mA.
- Unique echo wave processing technology can be used under various types of complex work conditions.
- Echo wave graphics display function, to display the signal waveform inside the tank, can be used for background noise processing.
- Operation Interface Language Selection: Traditional Chinese, Simplified Chinese, English. Capable of simulating output current signal of 4mA, 20mA.
- Support save back ground noise function, it could help to eliminate fake echoes.
- Support internal automatic temperature compensation.


## TEST STANDARDS

- High voltage :IEC60947-2
- Insulation resistance :IEC60092-504
- Power supply variation :IEC60092-504
- Power supply failure :IEC60092-504
- Electrical burst testing :IEC61000-4-4
- Voltage DIPS :IEC61000-4-11
- Humidity :IEC60068-2-30
- High/Low temperature test :IEC60068-2-38
- IP protection rating :IEC60529

## APPLICATION AREAS



- Power plant
- Chemical plant
- Cement plant
- Water treatment
- Paper mill plant
- Steel plant
- Refinery plant

# SPECIFICATION

Dimensions (Unit: mm)		
Model	<b>JTR301 Standard type</b>	
Medium of the material	Liquid	
Min. Dielectric (constant)	2.0	
Measuring range	6m	20m
Accuracy	±5mm or ±0.1% F.S. Whichever is greater	
Repeatability	±3mm or ±0.05% F.S. Whichever is greater	
Ambient temperature	-40~80°C(Applied for Ex-proof, as: ATEX · CSA · IECEx, NEPSI:-40~60°C)	
Operating temperature	-40~150°C	
Operating pressure	0~60Bar(25°C)	
Power supply	16~30Vdc Loop Power, 16~30Vdc 4-Wire	
Analog output	4~20mA	
Current distinguishability	1.6uA	
Load impedance	(Vs-16)/0.022 Ohm for 2-Wire, 300 Ohm for 4-Wire>16V	
Digital communication	Compatible with HART, Read Only for 2-Wire, RS485(Modbus) for 4-Wire	
Housing material	Aluminum alloy	
Protection rating	IP67	
Version	Rod type	Cable type
Minimum connection	3/4"PF	
Dead band	High constant coefficient ( $\epsilon > 10$ ) : Upper dead band<100mm · Lower dead band<50mm Low constant coefficient ( $\epsilon < 10$ ) : Upper dead band<500mm · Lower dead band<100mm	
Intrinsically safe parameters (option)	ATEX / CSA / IECEx / NEPSI, details please check chapter " Intrinsically safe parameters".	



※It shall combine with the ex-proof fence meeting level Ex ia to form the intrinsically safe system.

# SPECIFICATION

<p>Dimensions (Unit: mm)</p>		
Model	JTR301 High temp. type	
Medium of the material	Liquid	
Min. Dielectric (constant)	2.0	
Measuring range	6m	20m
Accuracy	±5mm or ±0.1% F.S. Whichever is greater	
Repeatability	±3mm or ±0.05% F.S. Whichever is greater	
Ambient temperature	-40~80°C(Applied for Ex-proof, as: ATEX · CSA · IECEx, NEPSI:-40~60°C)	
Operating temperature	-40~230°C	
Operating pressure	0~60Bar(25°C)	
Power supply	16~30Vdc Loop Power, 16~30Vdc 4-Wire	
Analog output	4~20mA	
Current distinguishability	1.6uA	
Load impedance	(Vs-16)/0.022 Ohm for 2-Wire, 300 Ohm for 4-Wire>16V	
Digital communication	Compatible with HART, Read Only for 2-Wire, RS485(Modbus) for 4-Wire	
Housing material	Aluminum alloy	
Protection rating	IP67	
Version	Rod type	Cable type
Minimum connection	3/4"PF	
Dead band	High constant coefficient ( $\varepsilon > 10$ ) : Upper dead band<300mm · Lower dead band<50mm Low constant coefficient ( $\varepsilon < 10$ ) : Upper dead band<500mm · Lower dead band<100mm	
Intrinsically safe parameters (option)	ATEX / CSA / IECEx / NEPSI , details please check chapter "Intrinsically safe parameters".	



※It shall combine with the ex-proof fence meeting level Ex ia to form the intrinsically safe system.

# SPECIFICATION

<p>Dimensions (Unit: mm)</p>		
Model	JTR302 Standard type	
Medium of the material	Solid	
Min. Dielectric (constant)	2.0	
Measuring range	6m	20m
Accuracy	±5mm or ±0.1% F.S. Whichever is greater	
Repeatability	±3mm or ±0.05% F.S. Whichever is greater	
Ambient temperature	-40~80°C(Applied for Ex-proof, as: ATEX · CSA · IECEx, NEPSI:-40~60°C)	
Operating temperature	-40~150°C	
Operating pressure	0~60Bar(25°C)	
Power supply	16~30Vdc Loop Power, 16~30Vdc 4-Wire	
Analog output	4~20mA	
Current distinguishability	1.6uA	
Load impedance	(Vs-16)/0.022 Ohm for 2-Wire, 300 Ohm for 4-Wire>16V	
Digital communication	Compatible with HART, Read Only for 2-Wire, RS485(Modbus) for 4-Wire	
Housing material	Aluminum alloy	
Protection rating	IP67	
Version	Rod type	Steel wire cable type
Minimum connection	1-1/2"PF	
Dead band	High constant coefficient ( $\epsilon > 10$ ) : Upper dead band<100mm · Lower dead band<50mm Low constant coefficient ( $\epsilon < 10$ ) : Upper dead band<500mm · Lower dead band<100mm	
Intrinsically safe parameters (option)	ATEX / CSA / IECEx / NEPSI , details please check chapter "Intrinsically safe parameters".	

※It shall combine with the ex-proof fence meeting level Ex ia to form the intrinsically safe system.



# SPECIFICATION

<p>Dimensions (Unit: mm)</p>		
Model	JTR302 High temp. type	
Medium of the material	Solid	
Min. Dielectric (constant)	2.0	
Measuring range	6m	20m
Accuracy	±5mm or ±0.1% F.S. Whichever is greater	
Repeatability	±3mm or ±0.05% F.S. Whichever is greater	
Ambient temperature	-40~80°C(Applied for Ex-proof, as: ATEX · CSA · IECEx, NEPSI:-40~60°C)	
Operating temperature	-40~230°C	
Operating pressure	0~60Bar(25°C)	
Power supply	16~30Vdc Loop Power, 16~30Vdc 4-Wire	
Analog output	4~20mA	
Current distinguishability	1.6uA	
Load impedance	(Vs-16)/0.022 Ohm for 2-Wire, 300 Ohm for 4-Wire>16V	
Digital communication	Compatible with HART, Read Only for 2-Wire, RS485(Modbus) for 4-Wire	
Housing material	Aluminum alloy	
Protection rating	IP67	
Version	Rod type	Steel wire cable type
Minimum connection	1-1/2"PF	
Dead band	High constant coefficient ( $\epsilon > 10$ ) : Upper dead band<300mm · Lower dead band<50mm Low constant coefficient ( $\epsilon < 10$ ) : Upper dead band<500mm · Lower dead band<100mm	
Intrinsically safe parameters (option)	ATEX / CSA / IECEx / NEPSI details please check chapter " Intrinsically safe parameters".	

※It shall combine with the ex-proof fence meeting level Ex ia to form the intrinsically safe system.




# SPECIFICATION

Dimensions (Unit: mm)		
Model	JTR305 Sandard type	JTR305 High temp. type
Medium of the material	Low Dielectric Liquid	
Min. Dielectric (constant)	1.6	
Measuring range	6m	
Accuracy	±5mm or ±0.1% F.S. Whichever is greater	
Repeatability	±3mm or ±0.05% F.S. Whichever is greater	
Ambient temperature	-40~80°C(Applied for Ex-proof, as: ATEX、CSA、IECEX、NEPSI:-40~60°C)	
Operating temperature	-40~150°C	-40~230°C
Operating pressure	0~60Bar(25°C)	
Power supply	16~30Vdc Loop Power, 16~30Vdc 4-Wire	
Analog output	4~20mA	
Current distinguishability	1.6uA	
Load impedance	(Vs-16)/0.022 Ohm for 2-Wire, 300 Ohm for 4-Wire>16V	
Digital communication	Compatible with HART, Read Only for 2-Wire, RS485(Modbus) for 4-Wire	
Housing material	Aluminum alloy	
Protection rating	IP67	
Version	Coaxial type	
Minimum connection	3/4"PF	
Dead band	High constant coefficient (ε>10) : Upper dead band<100mm · Lower dead band<50mm Low constant coefficient (ε<10) : Upper dead band<500mm · Lower dead band<100mm	
Intrinsically safe parameters (option)	ATEX / CSA / IECEX / NEPSI , details please check chapter "Intrinsically safe parameters".	

※It shall combine with the ex-proof fence meeting level Ex ia to form the intrinsically safe system.


# SPECIFICATION

Dimensions (Unit: mm)		
Model	<b>JTR30A Sanitary type</b>	
Medium of the material	Liquid	Solid
Min. Dielectric (constant)	1.6	
Measuring range	6m	
Accuracy	±5mm or ±0.1% F.S. Whichever is greater	
Repeatability	±3mm or ±0.05% F.S. Whichever is greater	
Ambient temperature	-40~80°C(Applied for Ex-proof, as: ATEX · CSA · IECEx, NEPSI:-40~60°C)	
Operating temperature	-40~150°C	
Operating pressure	0~60Bar(25°C)	
Power supply	16~30Vdc Loop Power, 16~30Vdc 4-Wire	
Analog output	4~20mA	
Current distinguishability	1.6uA	
Load impedance	(Vs-16)/0.022 Ohm for 2-Wire, 300 Ohm for 4-Wire>16V	
Digital communication	Compatible with HART, Read Only for 2-Wire, RS485(Modbus) for 4-Wire	
Housing material	Aluminum alloy	
Protection rating	IP67	
Version	Rod type	
Minimum connection	1"(3A)	2"(3A)
Dead band	High constant coefficient ( $\epsilon > 10$ ) : Upper dead band<100mm · Lower dead band<50mm Low constant coefficient ( $\epsilon < 10$ ) : Upper dead band<500mm · Lower dead band<100mm	
Intrinsically safe parameters (option)	ATEX / CSA / IECEx / NEPSI , details please check chapter "Intrinsically safe parameters".	

※It shall combine with the ex-proof fence meeting level Ex ia to form the intrinsically safe system.



# SPECIFICATION

Dimensions (Unit: mm)		
Model	<b>JTR30A Sanitary High temp. type</b>	
Medium of the material	Liquid	Solid
Min. Dielectric (constant)	1.6	
Measuring range	6m	
Accuracy	±5mm or ±0.1% F.S. Whichever is greater	
Repeatability	±3mm or ±0.05% F.S. Whichever is greater	
Ambient temperature	-40~80°C(Applied for Ex-proof, as: ATEX · CSA · IECEx, EPSI:-40~60°C)	
Operating temperature	-40~230°C	
Operating pressure	0~60Bar(25°C)	
Power supply	16~30Vdc Loop Power, 16~30Vdc 4-Wire	
Analog output	4~20mA	
Current distinguishability	1.6uA	
Load impedance	(Vs-16)/0.022 Ohm for 2-Wire, 300 Ohm for 4-Wire>16V	
Digital communication	Compatible with HART, Read Only for 2-Wire, RS485(Modbus) for 4-Wire	
Housing material	Aluminum alloy	
Protection rating	IP67	
Version	Rod type	
Minimum connection	1"(3A)	2"(3A)
Dead band	High constant coefficient ( $\epsilon > 10$ ) : Upper dead band<300mm · Lower dead band<50mm Low constant coefficient ( $\epsilon < 10$ ) : Upper dead band<500mm · Lower dead band<100mm	
Intrinsically safe parameters (option)	ATEX / CSA / IECEx / NEPSI , details please check chapter "Intrinsically safe parameters".	

※It shall combine with the ex-proof fence meeting level Ex ia to form the intrinsically safe system.

# INTRINSICALLY SAFE PARAMETERS

## ATEX 、 CSA 、 IECEx 、 TS:

Model series	Power circuit	Input entity parameters	Output entity parameters
JTR30XD	JLoop power 16~30Vdc X 2 with HART, by 2-core wire via terminal blocks J1 and J2	Loop power 1 In (V1+, V1-): $U_i = 30V$ $I_i = 100\text{ mA}$ $P_i = 0.7W$ $C_i = 0$ $L_i = 0$  Loop Power 2 In (V2+, V2-): Same as above	None
JTR30XB	Loop power 16~30Vdc with HART, by 2-core wire via terminal blocks J1	Loop power In (V+, V-): $U_i = 30V$ $I_i = 100\text{ mA}$ $P_i = 0.7W$ $C_i = 0$ $L_i = 0$	None
JTR30XH	4-Wire 16~30Vdc 4~20mA with RS485, by 2-core wire via terminal blocks J1 and J4  <div> <p>*Note: Feedback signal parameter for 'RS-485 In' is:  <math>U_o = 5.88V</math>  <math>I_o = 12.5mA</math>  <math>P_o = 18.5mW</math>  <math>C_o = 43\mu F</math>  <math>L_o = 3555\mu H</math></p> </div>	RS-485 In (D+, D-)*: $U_i = 12V$ $I_i = 100mA$ $P_i = 0.3W$ $C_i = 0$ $L_i = 0$  Power In (V+, V-): $U_i = 30V$ $I_i = 100mA$ $P_i = 0.7W$ $C_i = 0$ $L_i = 0$	Analog Out 1 (I+, I-): $U_o = 13.65V$ $I_o = 69mA$ $P_o = 0.236W$ $C_o = 0.79\mu F$ $L_o = 7468\mu H$ Through 2-core wire via terminal block J2  Analog Out 2 (I2+, I2-): $U_o = 13.65\text{ V}$ $I_o = 69mA$ $P_o = 0.236W$ $C_o = 0.79\mu F$ $L_o = 7468\mu H$ Through 2-core wire via terminal block J3
JTR30XE	4-Wire 16~30Vdc 4~20mA with RS485, by 2-core wire via terminal blocks J1 and J4  <div> <p>*Note: Feedback signal parameter for 'RS-485 In' is:  <math>U_o = 5.88V</math>  <math>I_o = 12.5mA</math>  <math>P_o = 18.5mW</math>  <math>C_o = 43\mu F</math>  <math>L_o = 3555\mu H</math></p> </div>	RS-485 In (D+, D-)*: $U_i = 12V$ $I_i = 100mA$ $P_i = 0.3W$ $C_i = 0$ $L_i = 0$  Power In (V+, V-): $U_i = 30V$ $I_i = 100mA$ $P_i = 0.7W$ $C_i = 0$ $L_i = 0$	Analog Out 1 (I+, I-): $U_o = 13.65V$ $I_o = 69mA$ $P_o = 0.236W$ $C_o = 0.79\mu F$ $L_o = 7468\mu H$ Through 2-core wire via terminal block J2
JTR30XF	4-Wire 5Vdc with RS485, by 2-core wire via terminal blocks J1 and J4  <div> <p>*Note: Feedback signal parameter for 'RS-485 In' is:  <math>U_o = 5.88V</math>  <math>I_o = 12.5mA</math>  <math>P_o = 18.5mW</math>  <math>C_o = 43\mu F</math>  <math>L_o = 3555\mu H</math></p> </div>	RS-485 In (D+, D-)*: $U_i = 12V$ $I_i = 100mA$ $P_i = 0.3W$ $C_i = 0$ $L_i = 0$  Power In (V+, V-): $U_i = 10V$ $I_i = 300mA$ $P_i = 0.7W$ $C_i = 0$ $L_i = 0$	None

# MEASURING RANGE

## NEPSI:

Terminal Code (Power)	Max. Voltage Input $U_i$ (V)	Max. Current Input $I_i$ (mA)	Max. Power Input $P_i$ (W)	Max. Internal equivalent parameter	
				$C_i$ ( $\mu$ F)	$L_i$ (mH)
V1+ · V1 - V2+ · V2 -	30	100	0.7	0	0
V+ · V-	30	100	0.7	0	0
	10	300			

Terminal Code (RS485)	Max. Voltage Input $U_i$ (V)	Max. Current Input $I_i$ (mA)	Max. Power Input $P_i$ (W)	Max. Internal equivalent parameter	
				$C_i$ ( $\mu$ F)	$L_i$ (mH)
D+ · D-	12	100	0.3	0	0
	Max. Voltage Output $U_o$ (V)	Max. Current Output $I_o$ (mA)	Max. Power Output $P_o$ (mW)	Max. External Parameter	
	7	15	25	$C_o$ ( $\mu$ F)	$L_o$ (mH)
				See below	

Terminal Code (AO)	Max. Voltage Input $U_i$ (V)	Max. Current Input $I_i$ (mA)	Max. Power Input $P_i$ (W)	Max. Internal equivalent parameter	
				$C_i$ ( $\mu$ F)	$L_i$ (mH)
I+ · I- I2+ · I2-	15	70	0.25	0	0
	Max. Voltage Output $U_o$ (V)	Max. Current Output $I_o$ (mA)	Max. Power Output $P_o$ (mW)	Max. External parameter	
	14	70	0.25	$C_o$ ( $\mu$ F)	$L_o$ (mH)
				See below	

Terminal Code	Total	
	$C_o$ ( $\mu$ F)	$L_o$ (mH)
D+ · D- I+ · I- I2+ · I2-	0.5	1.0

# MEASURING RANGE


JTR301 / JTR305				
Dielectric constant ( $\epsilon_r$ )	Typical liquids	Steel wire cable type	Rod type	Coaxial type
1.6~2.0	<ul style="list-style-type: none"> <li>● Liquefied gas, e.g. propane</li> <li>● Solvent</li> <li>● Freon</li> <li>● Palm oil</li> </ul>	Need special model with S5 type float		6m
2.0~2.5	<ul style="list-style-type: none"> <li>● Mineral oils, fuels</li> </ul>	12m	6m	6m
2.5~4.0	<ul style="list-style-type: none"> <li>● Benzene, styrene, toluene</li> <li>● Furan</li> <li>● Naphthalene</li> </ul>	14m	6m	6m
4.0~7.0	<ul style="list-style-type: none"> <li>● Chlorobenzene, chloroform</li> <li>● Cellulose spray</li> <li>● Isocyanate, aniline</li> </ul>	16m	6m	6m
> 7.0	<ul style="list-style-type: none"> <li>● Aqueous solutions</li> <li>● Alcohols</li> <li>● Ammonia</li> </ul>	20m	6m	6m

JTR302			
Dielectric constant ( $\epsilon_r$ )	Typical liquids	Steel wire cable type	Rod type
2.0~2.5	<ul style="list-style-type: none"> <li>● Portland cement</li> <li>● Plaster</li> <li>● Plastic granulate</li> </ul>	12m	6m
2.5~4.0	<ul style="list-style-type: none"> <li>● Grain, seeds</li> <li>● Flour</li> <li>● Ground stones</li> <li>● Sand</li> </ul>	14m	6m
4.0~7.0	<ul style="list-style-type: none"> <li>● Naturally moist stones, ores</li> <li>● Salt</li> </ul>	16m	6m
> 7.0	<ul style="list-style-type: none"> <li>● Metallic powder</li> <li>● Carbon black</li> <li>● Coal</li> </ul>	20m	6m

# FUNCTIONAL PRINCIPLE


## LIQUID LEVEL MEASUREMENT

High frequency microwave pulses travel along the steel wire cable or tube/rod. When they reach the medium surface, the microwave pulses are reflected. The pulse operating time is calculated and outputted by the electronic instrument of this meter as the liquid level height.



## BLIND AREA

The bench-mark of the measuring range is the thread or flange contact surface of the sensor. It should be noted that the measuring range is below the reference plane to the bottom of the induction rod and the upper and lower blind areas that cannot be measured. The default value, measuring range of this meter is set up with "water" as the test medium.



## BOTTOM SIGNAL ENHANCEMENT & TRACKING TECHNOLOGY

This sensor is equipped with bottom sensing detection tracking mode, when the measured medium has a low dielectric constant, in order to increase the sensitivity. This feature is useful such as in the plastic particles, packing chips or in liquefied containers. When the dielectric constant is between 3 and 10, as long as the echo wave signal cannot be detected, the bottom sensing detection tracking function will be automatically activated.

The calculation of the measured value uses the dielectric constant last recorded; the accuracy of the meter depends on the stability of the dielectric constant.


If the medium's dielectric constant is less than 3, the bottom sensing detection tracking function is automatically activated throughout the process. The medium's dielectric constant must be input as a stable dielectric constant is important in the measurement.

※ Please refer to product manual for details of setting.

# FUNCTIONAL PRINCIPLE

## DUAL LIQUID LEVEL INTERFACE MEASUREMENT

High frequency microwave pulses travel along the steel wire cable or tube/rod. When they reach the medium surface, part of the microwave pulses are reflected. The other part penetrates through the upper layer of medium and generates the second reflection at the interface between upper and lower layers of the medium. Two pulse operating time periods are calculated and outputted by the electronic instrument of this meter as the dual liquid level heights.



Dual Liquid Level Interface Measuring Condition:

Upper layer medium (L2):

The upper layer medium must be nonconductive dielectric; the dielectric constant of upper layer medium or the actual distance to interface must be known; the dielectric constant of the upper layer medium needs to be greater than 1.6.

The upper layer medium must be stable and the medium cannot be changed or mixed; the upper layer medium must be uniform, and the minimum thickness of the upper layer medium without layering shall be greater than 50 mm (1.97 inches) and clearly separated between the upper layer and lower layer mediums. If there is emulsion phase or debris layer, the maximum thickness shall not be greater than 50 mm (1.97 inches), better measuring results can be achieved without foam on the surface if possible.

Lower layer medium (L1):

The dielectric constant of lower layer must be 10 greater than the dielectric constant of lower layer, preferably conductive medium.

For example, if the dielectric constant of upper layer is 2, the dielectric constant of lower layer shall be at least 12.

Gas layer (L3):

This layer is the mixture of air or gas

Dual Liquid Level Interface Measurement output signal setting:

The meter shall be set up for using in "Separate layers interface measurement", used in interface measurement of two types of liquid, dual analog output version can be selected and adjusted in the setting menu.

# INSTALLATION INFORMATION

Please note that when installing the JTR3 series product in a metal container, the spacing from the other devices in the container shall be at least 300 mm (12 in).

When installing in a non-metal container, the spacing from the container wall shall be at least 500 mm (19.7 in).


It is necessary to ensure the probe must not touch any device or tank wall during operation.

It is recommended to fix the bottom of the probe in the tank to reduce the probe shaking when using steel wire cable type induction probe.

Please note that this instrument has upper and lower blind areas that it is disable to measure the full end of probe..


When the welding operation is required during the installation process, please remove the electronic module of the sensor from the terminal box before starting the welding work to avoid damage to the electronic equipment due to induction coupling or other failures.

When used in plastic/glass containers, it is necessary to use the meter type with flange or place a piece of metal plate ( $\phi > 200\text{mm}$  / 8in) under the processing connection when mounted. The metal plate shall be directly contacted with the processing connection.



During installation, please avoid using the extended nozzle on the container. Please install the sensor leveled with the top of the container as possible. If this cannot be done, please use a shorter extended nozzle.

Please do not install this instrument at the inlet to ensure that the sensor is in a stable position in the medium and not in the inflow position of the liquid to avoid false measurements when the liquid flows in.







# WIRING DIAGRAM

## 2-wire type

JTR30XD series




JTR30XB series




Note! For 2-wire loop power type: when equipped with two sets of analog outputs, each circuit should be operated independently. Parallel connection of the two circuits will cause abnormal current output.

## 4-Wire type


JTR30XH series



JTR30XE series



JTR30XF series



## MODEL NUMBER / ORDER CODE COMPARISON TABLE

Model Number	Order Code
JTR301	JTR1□□□□-A1 JTR1□□□□-A2
JTR302	JTR1□□□□-B1 JTR1□□□□-B2
JTR305	JTR1□□□□-A3
JTR30A	JTR103□□-E1

# ORDERING INFORMATION

	05	06	07	08	09	10	11	12	13	14	15	16	17	18	19	20	21	22	23	
<b>JTR1</b>																				
<b>05 06 Model</b>																				
00: Standard																				
02: Hi-temperature																				
03: Sanitary																				
32: Sanitary+ Hi-temperature type																				
<b>07 08 Certification</b>																				
00: None																				
1B: ATEX-Ex ia																				
2B: IECEx-Ex ia																				
6B: CSA																				
7B: NEPSI-Ex ia																				
<b>09 10 Probe Type</b>																				
A1: Rod type for liquid 6mm																				
A2: Steel wire cable type for liquid 4mm																				
A3: Coaxial type 21.7mm																				
B1: Rod type for solid																				
B2: Cable type for solid																				
E1: Sanitary rod																				
<b>11 12 Probe material</b>																				
MA: SUS 304																				
MC: SUS 316L																				
<b>Connection</b>																				
<b>13 14</b>					<b>15 16</b>				<b>17 18</b>											
Flange					A7: 3/4"				00: None											
AJ: JIS-RF					A8: 1"				01: PT male											
AN: ANSI-RF					B1: 1-1/2"				03: PF male											
AR: DIN-RF					B2: 2"				07: NPT male											
AI : 3A					B5: 3"				13: GAS male											
					B7: 4"				40: 5 kg/cm <sup>2</sup>											
Thread					E1: DN40				48: 150 Lbs											
AA: JIS									56: PN 6											
AC: ANSI									57: PN10											
									59: PN25											

(Next page)



**JTR1** <sup>05</sup> <sup>06</sup> <sup>07</sup> <sup>08</sup> - <sup>09</sup> <sup>10</sup> <sup>11</sup> <sup>12</sup> <sup>13</sup> <sup>14</sup> <sup>15</sup> <sup>16</sup> <sup>17</sup> <sup>18</sup> <sup>19</sup> <sup>20</sup> <sup>21</sup> <sup>22</sup> <sup>23</sup>

<sup>19</sup> **Output/input**

B: Loop Power 16 ~ 30 Vdc with HART  
D: Loop Power 16 ~ 30 Vdc X 2 with HART  
E: 4-Wire 16 ~ 30Vdc 4~20mA with RS485  
H: 4-Wire 16 ~ 30Vdc, 4~20mA X2 with Rs485  
F: 5~10 Vdc, only RS485

<sup>20</sup> <sup>21</sup> <sup>22</sup> <sup>23</sup> **Length**

Code	Probe Length
0500~6000	500~6000mm
0500~A200	500~20000mm

# JTR Radar Level Transmitter

## Customer Information

Prepared by: \_\_\_\_\_ Date: \_\_\_\_\_

Company: \_\_\_\_\_ Industry: \_\_\_\_\_

E-mail: \_\_\_\_\_ Phone Number: \_\_\_\_\_

Address: \_\_\_\_\_

## Application Information

### B.1 Measuring Material Information

Application Description:

Installation Area:	<input type="checkbox"/> Storage tank	<input type="checkbox"/> Process tank	<input type="checkbox"/> Open-air application	
Material Status :	<input type="checkbox"/> Liquid	<input type="checkbox"/> Slurry/ Sludge/ Paste	<input type="checkbox"/> Solid/ Granulate/Grain	<input type="checkbox"/> Powder
Material Name :		Dielectric Constant	<input type="checkbox"/> 1.4~1.9	<input type="checkbox"/> 4.0~10.0
			<input type="checkbox"/> 2.0~2.5	<input type="checkbox"/> > 10
			<input type="checkbox"/> 2.6~4.0	<input type="checkbox"/> Unknow

### B.2 Power Supply

☐ DC : \_\_\_\_\_ ☐ AC : \_\_\_\_\_

### B.3 Output Signal

Analog : ☐ 4~20 mA-4 Wire ☐ 4~20mA 2-Wire ☐ Other  
Digital : ☐ RS-485 ☐ HART ☐ Other

### B.4 Measuring range

Measuring range: \_\_\_\_\_ meters

### B.5 Measuring Condition

Operating Temperature

Max: \_\_\_\_\_ Min: \_\_\_\_\_ °C

Ambient Temperature

Max: \_\_\_\_\_ Min: \_\_\_\_\_ °C





Operating Pressure

Max: \_\_\_\_\_ Min: \_\_\_\_\_ °C


### B.6 Connection

Connection: ☐ Threaded ☐ Flange  
Size and Standard: \_\_\_\_\_ Flange Material: \_\_\_\_\_

## B.7 Tank Information

Tank Shape	<input type="checkbox"/> Vertical Cylinder	<input type="checkbox"/> Horizontal Cylinder	<input type="checkbox"/> Spherical	
	<input type="checkbox"/> Cubical/rectangular	<input type="checkbox"/> Other: _____		
Tank Material	<input type="checkbox"/> Metal	<input type="checkbox"/> Plastic	<input type="checkbox"/> Cement	<input type="checkbox"/> Other _____
Tank Bottom	<input type="checkbox"/> Flat			
	<input type="checkbox"/> Dish			
	<input type="checkbox"/> Cone			
	<input type="checkbox"/> Other (Please describe)	_____ _____		
Tank Tank Height (H): _____ m Tank Diameter (W): _____ m Cone Height (H1): _____ m (Ignore cone height with flat/disk bottom )				
Radar Distance to tank wall(D1): _____ m				
Nozzle <input type="checkbox"/> Yes Nozzle Diameter (L): _____ m Nozzle Height (D): _____ m <input type="checkbox"/> NO				
Agitator <input type="checkbox"/> Yes Distance to rada (D2): _____ m <input type="checkbox"/> NO				
Ladder <input type="checkbox"/> Yes Distance to rada (D3): _____ m <input type="checkbox"/> NO				
Heater <input type="checkbox"/> Yes <input type="checkbox"/> NO				
Other Internal Obstacles <input type="checkbox"/> Yes <input type="checkbox"/> NO				

# SUCCESS STORY



Water purification barrel



Copper sulfate storage tank



High temperature boiler



Food factory - bean dregs storage barrel



# Global Network



## ■ Head Quarter

- Taiwan  
**FineTek Co., Ltd. - Taipei Head Quarter**   
No.16, Tzuchiang St., Tucheng Industrial Park  
New Taipei City 236, Taiwan  
TEL: 886-2-2269-6789  
FAX: 886-2-2268-6682  
EMAIL: info@fine-tek.com

## ■ North America

- California, U.S.  
**Aplus Finetek Sensor Inc. - US Office**  
355 S. Lemon Ave, Suite D  
Walnut, CA 91789  
TEL: 1 909 598 2488  
FAX: 1 909 598 3188  
EMAIL: info@aplusfine.com

## ■ Europe

- Germany  
**FineTek GmbH - Germany Office**  
Bei den Kämpen 26  
21220 Seevetal-Ramelsloh, Germany  
TEL: +49-(0)4185-8083-12  
FAX: +49-(0)4185-8083-80  
EMAIL: info@fine-tek.de

## ■ Asia

- China  
**Fine automation Co., Ltd. - Shanghai Factory**   
No.451 DuHui Rd, MinHang District, Shanghai,  
China 201109  
TEL: 86-21-6490-7260  
EMAIL: info.sh@fine-tek.com

- Singapore  
**FineTek Pte Ltd. - Singapore Office**  
37 Kaki Bukit Place, Level 4 Singapore 416215  
TEL: 65-6452-6340  
EMAIL: info.sg@fine-tek.com

- Indonesia  
**PT. FineTek Automation Indonesia - Indonesia Office**   
PERGUDANGAN TUNAS BITUNG  
JL. Raya Serang KM. 13,8, Blok C3 No. 12&15,  
Bitung Cikupa, Tangerang 15710  
TEL: 62 (021)-2958-1688  
EMAIL: info.id@fine-tek.com

- Müttec Instruments GmbH - Germany Office   
Bei den Kämpen 26  
21220 Seevetal-Ramelsloh, Germany  
TEL: +49-(0)4185-8083-0  
FAX: +49-(0)4185-8083-80  
EMAIL: muetec@muetec.de



Distributor: